FOREST TRIM.

Fingerjoint | Primed | Exterior Trim



Real Performance.
Real Value.

Real Wood.

Exclusively from...



The Forest Trim Advantage



IWP offers Forest Trim in a variety of dimensions including:

- 1 x 2 thru 1 x 12
- 5/4 x 3 thru 5/4 x 12
- 2 x 2 thru 2 x 12
- 2 x 3 Sill Stock

Forest Trim's Long length structure means fewer joints on the job site, saving time and money while improving the finished appearance.

Forest Trim features a triple priming process in a controlled environment to ensure consistent coverage. This results in a product that is paint-ready for 2 coats of Exterior Latex Paint.

VERSATILITY

- Wide range of dimensions for any application
- Long lengths for fewer joints on the job site
- Reversible for smooth or resawn appearance

SUSTAINABILITY

 Forest Trim is sourced from responsibly managed cypress forests

STABILITY

- Engineered to last for years of performance
- Sealed knots for long-term beauty and performance
- · 25 year warranty
- Natural resistance to insect & fungal attacks

The Forest Trim Difference

Forest Trim is a fingerjointed, edge-glued and primed exterior trim offering a unique combination of stability, versatility, environmental responsibility, and value.

With natural resistance to decay and rot, Forest Trim offers the ideal substrate for outdoor applications.

Forest Trim is sourced from responsibly managed forests to support the market-driven quest for sustainable products.

What does this mean for you? With Forest Trim you get a superior product with years of proven performance to meet the needs of professional contractors and homeowners alike!

Storage, Finishing and Installation

Forest Trim is installed according to industry standards for wood trim. As with all wood products, it is recommended that Forest Trim acclimate to your building site for a minimum of seven days.

Forest Trim should be stored in a dry location off the ground and protected from direct sunlight, water saturation & dirt prior to installation.

Forest Trim should be fastened with stainless steel or hot dipped galvanized nails and requires two coats of exterior latex paint.

Complete storage, handling, and finishing instructions are available from your IWP salesperson.





Locations

Clackamas

14421 SE 98th Court Clackamas, OR 97015 503.650.9663 | 800.875.9663

7 | 900 975 9667 | F/1 779 7717

1271 Stowe Avenue Medford, OR 97501 541.779.7717 | 800.262.7717

Medford

Tumwater

8277 Center St. S.W. Tumwater, WA 98501 360.352.9669 | 877.830.9663

Cloverdale

280 Asti Road Cloverdale, CA 95425 707.433.3313 | 800.371.0637

Post Falls

4074 E. Horsehaven Ave. Post Falls, ID 83854 208.586.9701



www.iwpllc.com

